SYNTEL
Smart Telereturns

NEO DX
308 / 412
Small on Price
Big on Features

TEC CERTIFIED

Small entrepreneurs & establishments require a communication system that offers all the basic functionalities of an intercom, coupled with some hi-end features of an EPABX, at a price that fits in within their tight budgets. Recognizing these specific requirements, Syntel designed a new age mini EPABX that provides all the required and essential features in-buit in the system at a price far less than any other equally competent model in the market. Thus not only does the NEO-Dx series systems ensure a true value for money preposition but also acts as a true productivity enhancement tool in ones day to day telecommunication processes by offering all the features that one could possible need in skin with the basic model.

With more than 50 features to help your organization improve its productivity through better telecommunication, it is the TRUE VALUE FOR MONEY product.

Unique Features

- Auto call back on extension & CO
- Abbreviated dialing (system & Personal)
- Alarms (User)
- Call Consult
- Barge-in (with & without tone)
- Barge-in protection
- Class of service
- Call transfer
- Call forward Unconditional / on busy / on no reply-internal
- Call forward protect
- Call split after conference
- Call follow me
- Call park
- Call pick-up (Selective / Group) - 3 Groups
- Conference - 3 party
- CLI - Caller Line Identification (Both DTMF / FSK)
- CO Access

- CO programming
- CO type definition & grouping
- Day / night mode (automatic / manual)
- Direct inward dialing
- Do not disturb override
- Dynamic STD Locking
- Forward DID extension
- Hotline 2 types
- Hunting patterns - 3 types
- Last number redial
- Password protection (Extension & programming)
- PFCT - 2 port
- Real time clock
- Status display (CO)
- Selective CO Seizure
- Voice guidance (Optional)
- Walk-in-class of service

Technical Specification

	NEO-Dx 308	NEO-Dx 412
System Structure	3 Analog Trunks	4 Analog Trunk
Capacity	8 Extensions	12 Extensions
Configuration	Supports FSK CLI	
	System is able to configure 8 / 12 Extensions - Fixed	
	System is able to interface 3 / 4 Analog Trunks - Fixed	
	Supports single / two / three digits Ext. Nos. (2, 3, 4, 5 series)	
	Operator & Master Extension (20 & 21 Resp.)	
	4 Distinct messages for 6 various events of 10 Sec. each	
Input Operating Voltage	Operates on Linear PSU at 180Vac ~ 250Vac 50 Hz	
Power Backup	UPS / Invertor	
Voice Guidance	Single channel voice guidance	
Extension Numbers	2 / 3 / 4 / 5 digit Extension numbers	
Dimensions	(L x W x H) : 297 x 210 x 80 mm	
Power Consumption	Maximum 25W	

*EMC–EMI and safety test certified from accredited laboratory.

Enterprise Communication | Security & Surveillance | AV Integration & Automation | Network Infrastructure | Integrated Software Applications